

Revolabs FLX UC 500

USB Conference Phone for Enterprise

Softphones, Messenger, and Video Conferencing Applications are supplementing or replacing conventional telephony systems for Enterprise Communications.

Current audio solutions for the enterprise are primitive or provide poor audio performance. Leveraging the built-in laptop speaker and microphone causes users to have difficulty hearing and being heard. Alternatively, solutions powered via USB have limited audio output volume.

This is especially cumbersome and inconvenient for conference rooms with multiple participants crowding around a single computer or device.

The Revolabs FLXTM UC 500 provides the solution for **enterprise communications.** Combining the best technology for speakers, microphones, and audio processing, the UC 500 improves all aspects of audio handling for your communication needs. It provides "Best in Class" audio performance, changing the price/performance paradigm in this space.

The UC 500 is a **full duplex system** allowing for audio playback and audio capture simultaneously. Users communicate as if they were in the same room, allowing for the natural flow of conversation and interruptions, and the technology in the UC 500 ensures that every part of that discussion is heard.

The UC 500 provides exceptional audio quality through the tweeter and mid-woofer speaker elements. As a powered system, the speakers' output audio fill the conference room with sound ensuring that the participant can be heard — whether the system is in an executive office, huddle room, or a conference room.

Four embedded microphones give the UC 500 full 360° coverage of audio capture. The microphones feature wideband frequency response, making the UC 500 the ideal solution for any communication application. You can hear every word of your softphone call, webinar, or audio conference call, and be assured that the far end will hear you clearly as well.

The UC 500 provides integrated acoustic echo cancellation; no additional processing is required by the computer to ensure the best possible audio signal.

With years of experience building audio solutions for executive conference rooms, Yamaha Unified Communications has incorporated this technology into the design of the UC 500. The UC 500 has been designed and rigorously tested in real conference rooms to ensure every piece of the system – from the mechanical design, to the electrical design, to the signal processing, to the product firmware – is optimized for acoustic performance. The UC 500 offers new possibilities to enhance the experience of using unified communications solutions for meetings and online collaboration.

Benefits

FILLS THE CONFERENCE ROOM WITH HIGH **OUALITY SPEAKER SOUND**

In conference rooms sized for up to 8-10 people, speaker audio can be heard by every meeting participant; the UC 500's powerful speaker can fill the entire conference room with crystal-clear audio.

COMPLETE 360° ROOM MICROPHONE COVERAGE

Every word by the meeting participants is picked up and transmitted to the far end by the four embedded directional microphones.

FULL DUPLEX

Participants on every endpoint can communicate naturally as if they are in the same room; the technology in the UC 500 supports simultaneous audio playback and audio capture ensuring every word is heard.

THIRD-PARTY APPLICATION SUPPORT

Easily integrates with your choice of 3rd party applications for collaboration and conferencing; the additional FLX UC Device Manager provides call control for hang up and answer directly from the device using the intuitive capacitive touch buttons.

INTEGRATED ACOUSTIC ECHO CANCELLATION

The meeting participant speaking has his audio picked up and transmitted clearly. Built-in digital signal processing separates the speech of the meeting participant from the room noise and audio output from the speakers to ensure only the correct audio is transmitted to the far end. Real discussions between conference participants are finally possible.

STYLISH AND FUNCTIONALLY DESIGNED FOR **SMALL SPACES**

Innovative design provides quality audio in a smaller form factor, taking up less table space.

FEATURES AND SPECIFICATIONS

Speaker Elements Speaker Frequency Response MAX SPL Microphones Microphone Coverage Microphone Frequency Response Echo Cancellation Full Duplex

Tweeter, Mid-Woofer 160 - 20.000 Hz91 dB at 1m 4 embedded directional 360° Audio Pick-Up 160 - 16.000 Hz Individual AEC per microphone

INTERFACES

Power **USB** AC Power Adapter Mini USB 2.0 Connector

ENVIRONMENTAL

Operating Temperature Storage Temperature Relative Humidity 32 - 104 °F (0 - 40 °C) -22°F to +131 °F (-30°C to +55 °C) 20%-85% (noncondensing)

COMPLIANCE

Safety

CE Mark: EN 60950 IEC 60950 LII 60950 CSE C22.2, No. 60950

EMC AS/NZS 60950 ICES-003 Class B EN55022 Class B

CISPR22 Class B AS/NZS CISPR22 Class B VCCI Class B

EN55024

Environmental

RoHS

SIZE, WEIGHT, POWER

Height Width Length Weight Power

4.84in (123mm) 5.9in (150mm) 5.9 in (150mm) 2.2lb (1 kg)

15V, 1A External Power Supply

WARRANTY

1 year warranty* *EU warranty is 2 years



- - 1 USB Cable, 6.56ft (2.0m)
- 1 AC Power Adapter
- Plug Clips
- Quick Start Guide



Yamaha Unified Communications, Inc.

144 North Road #3250 Sudbury, MA 01776 USA +1 800-326-1088 uc-sales@music.yamaha.com

Yamaha UC EMEA

190 High Street Tonbridge, Kent TN9 1BE, UK +44 (0)1732 366535 uc-salesemea@music.yamaha.com

Yamaha UC APAC

+852.8108.8820 uc-salesapac@music.yamaha.com